


The perfect top-quality wheel for every surface and every application: Choose from a wide range of wheel versions with the same diameter – they are fully interchangeable. The last two digits of the hand truck's type number usually indicate the wheel version. With pneumatic tyres, the carcass structure ensures highest loading with minimum rolling resistance. All wheels are odourless and are fitted with two water and dust-proof deep-groove ball bearings.

One-piece EXLAN wheel rim, with two water and dust-proof deep-groove ball bearings, tool-free mounting – the tyre is simply pushed onto the rim and secured with the circular clip.



EXLAN wheel rim

Pneumatic tyre with radial tread and minimum rolling resistance, excellent shock absorption also on rough surfaces




No. 21
Ø 260 mm

Pneumatic tyre with lug tread and low rolling resistance, excellent shock absorption also on rough surfaces



No. 22
Ø 260 mm

Pneumatic tyre with radial tread, light grey and non-marking on sensitive floors, minimum rolling resistance, excellent shock absorption




No. 23
Ø 260 mm

Heavy-duty pneumatic tyre with reinforced radial tread, minimum rolling resistance, excellent shock absorption also on rough surfaces



No. 24
Ø 260 mm

AIRLEX, light grey and non-marking, foamed polyurethane with radial tread, no risk of a flat tyre, excellent shock absorption, low rolling resistance, extremely long service life



No. 25
Ø 260 mm

Pneumatic tyre with rib tread and low rolling resistance, excellent shock absorption also on rough surfaces



No. 01
Ø 260 mm

Airelastik flat tread, highly elastic two-component tyre, silent and smooth running, good shock absorption, light grey and non-marking



No. 62
Ø 260 mm

Smooth-running flat tread, highly elastic, silent running, very low rolling resistance



No. 66
Ø 260 mm

Airelastik flat tread, light grey, highly elastic two-component tyre, silent and smooth running, good shock absorption, non-marking on sensitive floors



No. 42
Ø 200 mm

Smooth-running flat tread, good elasticity, silent running, low rolling resistance



No. 44
Ø 200 mm

Airelastik flat tread, light grey, highly elastic two-component tyre, silent and smooth running, good shock absorption, non-marking on sensitive floors




No. 74
Ø 200 mm

Smooth-running flat tread, highly elastic, silent running, very low rolling resistance



No. 76
Ø 200 mm

Airelastik flat tread, light grey, highly elastic two-component tyre, silent and smooth running, good shock absorption, non-marking on sensitive floors



No. 71
Ø 175 mm

Smooth-running flat tread, good elasticity, silent running, low rolling resistance



No. 05
Ø 160 mm